

PYCKO SCIENTIFIC LIMITED

31 London Road, Grantham, NG31 6EX
Telephone 01476 401992
e-mail: bill@pycko.co.uk
www.pycko.co.uk

Your Alternative
To The Obvious

Gamma Area Monitor - Model 375/2

- **Affordable Area Monitor**
- **Integrated Design**
- **Battery Backup**
- **Networkable**
- **Audio & Visual Alarms**



The Model 375/2 Digital Wall-Mount Area Monitor is designed for visibility and ease of use. This monitor incorporates an internally housed energy compensated GM detector with a range from 1 uSv/hr to 10 mSv/hr. Featuring a wall-mount chassis, and has a four-digit LED display that is readable from thirty feet away. Backlit indicators warn of low radiation alarm (yellow), high radiation alarm (red), instrument failure (red) and low battery (yellow). A green status light is a positive indication of instrument operation. Parameters are protected under a calibration cover. Calibration is easily accomplished by moving the cal dipswitch to the right, and using the pushbuttons to increment or decrement the calibration constant, dead time correction and alarm point parameters. Parameters are stored in non-volatile memory (retained even with power disconnected). A five-decade logarithmic analogue output is provided. A battery backup provides 48 hours of additional use after the primary power is turned off.

INDICATED USE:	General purpose area monitor
DETECTION RANGE:	1 uSv/hr to 10 mSv/hr
DETECTOR TYPE:	Internally mounted energy compensated GM
SIZE:	18.7 x 24.6 x 6.4 cm
WEIGHT:	2.3 kg